



CATALOGO

ALLUMINIO

ALLUMiniO e LeGHe - LAMinATi

LAMieRe MANDORLATE A 5 MANDORLe
en AW-1200

Spessore mm	Formato mm	Peso teorico unit. Kg	Stato fisico			
			F			
2	1000x2000	12,7	✓			
2	1250x2500	19,8	✓			
2	1250x3000	23,8	✓			
2	1500x3000	29	✓			
2	2000x3000	37,2	✓			
2	2000x4000	49,6	✓			
2	2000x6000	74,4	✓			
2,5	1000x2000	15,4	✓			
2,5	1250x2500	24,0	✓			
2,5	1250x3000	28,1	✓			
2,5	1500x3000	33,7	✓			
3	1000x2000	18,0	✓			
3	1000x2500	22,5	✓			
3	1000x3000	27,1	✓			
3	1250x2500	28,2	✓			
3	1250x3000	33,9	✓			
3	1250x3500	38,9	✓			
3	1500x2500	33,8	✓			
3	1500x3000	40,6	✓			
3	1500x3500	46,7	✓			
3	1500x4000	54,1	✓			
3	1500x6000	81,2	✓			
3	2000x3000	53,4	✓			
3	2000x4000	72,0	✓			
3	2000x5000	89,0	✓			
3	2000x6000	108,0	✓			

LAMieRe MANDORLATE A 5 MANDORLe
PeRALUMAn en AW-5754

Spessore mm	Formato mm	Peso teorico unit. Kg	Stato fisico			
			H114			
2	1000x2000	14,4	✓			
2	1250x2500	18,7	✓			
2	1500x3000	27,0	✓			
2,5	1000x2000	15	✓			
2,5	1000x3000	22,5	✓			
2,5	1250x2500	23,4	✓			
2,5	1250x3000	28,1	✓			
2,5	1500x3000	33,7	✓			
2,5	2000x4000	60	✓			
2,5	2000x6000	90	✓			
3	1000x2000	17,8	✓			
3	1250x2500	28,2	✓			
3	1500x3000	40,6	✓			
5	1000x2000	29,0	✓			
5	1250x2500	45,1	✓			
5	1500x3000	65,0	✓			

LAMinATi PRVerniciATI cOILS
cOn PeLABiLe (en AW-3105) H43

Spessore mm	Larghezza mm		Peso teorico Kg/MI	colore
1	1250	✓	3,37	Bronzo
1,2	1250	✓	4,05	Bronzo
1,2	1250	✓	4,05	Elettrocolore
1,2	1500	✓	4,86	Elettrocolore
0,8	1250	✓	2,70	Silver
1	1000	✓	2,70	Silver
1	1250	✓	3,37	Silver
1	1500	✓	4,05	Silver
1,2	1250	✓	4,05	Silver
1,2	1500	✓	4,86	Silver
1,4	1000	✓	3,78	Silver
1,4	1250	✓	4,73	Silver
1,4	1500	✓	5,67	Silver
0,8	1250	✓	2,70	RAL 1013 Crema
1	1250	✓	3,37	RAL 1013 Crema
1,2	1250	✓	4,05	RAL 1013 Crema
0,8	1250	✓	2,70	RAL 9010 Bianco
1	1250	✓	3,37	RAL 9010 Bianco
1	1500	✓	4,05	RAL 9010 Bianco
1,2	1250	✓	4,05	RAL 9010 Bianco
1,2	1500	✓	4,86	RAL 9010 Bianco
1,2	1250	✓	4,05	RAL 5010 Blu
1,2	1250	✓	4,05	RAL 3003 Rosso
1,2	1500	✓	4,86	RAL 3003 Rosso
1,2	1250	✓	4,05	RAL 6005 Verde
1,2	1500	✓	4,86	RAL 6005 Verde
1,2	1250	✓	4,05	RAL 1021 Giallo
1,2	1250	✓	4,05	TDM
1,2	1250	✓	4,05	RAL 9005 Nero
1,2	1500	✓	4,86	RAL 9005 Nero
1,5	1250	✓	5,06	RAL 9010 Bianco
1,5	1500	✓	6,07	RAL 9010 Bianco
2	1250	✓	6,75	RAL 9010 Bianco
2	1500	✓	8,10	RAL 9010 Bianco

LAMinATi AnOdIZZATI ARGEnTO
cOn PeLABiLe (en AW-5005)

Spessore mm	Formato mm	Peso teorico Kg/MI (*) unitario	Stato fisico			
			H24 H34			
0,5	1000x2000	2,70 (*)	✓			
0,6	1000x2000	3,24 (*)	✓			
0,8	1000x2000	4,32 (*)	✓			
1	1000x2000	5,40 (*)	✓			
1	1250x2500	8,43 (*)	✓			
1	1500x3000	12,15 (*)	✓			
1,2	1000x2000	6,48 (*)	✓			
1,2	1250x2500	10,12 (*)	✓			
1,2	1500x3000	14,58 (*)	✓			
1,5	1000x2000	8,10 (*)	✓			
1,5	1250x2500	12,66 (*)	✓			
1,5	1500x3000	18,22 (*)	✓			
2	1000x2000	10,80 (*)	✓			
2	1250x2500	16,87 (*)	✓			
2	1500x3000	24,30 (*)	✓			
2,5	1000x2000	13,50 (*)	✓			
2,5	1250x2500	21,09 (*)	✓			
2,5	1500x3000	30,37 (*)	✓			
3	1000x2000	16,20 (*)	✓			
3	1250x2500	25,31 (*)	✓			
3	1500x3000	36,40 (*)	✓			
1	1250 Coils	3,37	✓			
1	1500 Coils	4,05	✓			
1,2	1250 Coils	4,05	✓			
1,5	1500 Coils	6,07	✓			
2	1500 Coils	8,10	✓			

LAMieRe MANDORLATE TIPO "CHICCO GRS"
PeRALUMAn en AW-5754

Spessore mm	Formato mm	Peso teorico unit. Kg	Stato fisico			
			H224			
1,5	1250x2500	14,4	✓			
2	1250x2500	19	✓			

MALTERINI A. METALFERRO

PeRALUMAn

LAMieRe

Lega	Spessore formato mm	Peso teorico unit. Kg	Stato fisico			
			H111	0	H32	H34
EN AW-5754 1	1000x2000	5,40	✓		✓	
EN AW-5754 1	1250x2500	8,40	✓		✓	
EN AW-5754 1	1500x3000	12,20	✓		✓	
EN AW-5754 1,2	1000x2000	6,40	✓		✓	
EN AW-5754 1,2	1250x2500	10,10			✓	
EN AW-5754 1,2	1500x3000	14,60	✓		✓	
EN AW-5754 1,5	1000x2000	8,10	✓		✓	
EN AW-5754 1,5	1250x2500	12,60	✓		✓	
EN AW-5754 1,5	1500x3000	18,20	✓		✓	
EN AW-5754 2	1000x2000	10,80	✓		✓	
EN AW-5754 2	1250x2500	16,80	✓		✓	
EN AW-5754 2	1500x3000	24,30	✓		✓	
EN AW-5754 2,5	1000x2000	13,50	✓			
EN AW-5754 2,5	1250x2500	21,10	✓		✓	
EN AW-5754 2,5	1500x3000	30,40	✓		✓	
EN AW-5754 3	1000x2000	16,20	✓		✓	
EN AW-5754 3	1250x2500	25,20	✓		✓	
EN AW-5754 3	1500x3000	36,40	✓		✓	
EN AW-5754 3	1500x3500	42,50	✓			
EN AW-5754 4	1000x2000	21,60	✓		✓	
EN AW-5754 4	1250x2500	33,80	✓		✓	
EN AW-5754 4	1500x3000	48,60	✓			
EN AW-5754 5	1000x2000	27,00		✓	✓	
EN AW-5754 5	1250x2500	42,20	✓		✓	
EN AW-5754 5	1500x3000	60,80	✓			
EN AW-5754 6	1000x2000	32,40		✓		
EN AW-5754 6	1250x2500	50,60	✓			
EN AW-5754 6	1500x3000	72,90	✓		✓	
EN AW-5754 8	1000x2000	43,20	✓			
EN AW-5754 8	1250x2500	67,50	✓			
EN AW-5754 8	1500x3000	97,20	✓			
EN AW-5754 10	1000x2000	54,00		✓		
EN AW-5754 10	1500x3000	122,00	✓			

LAMieRe e PIASTRe

Lega	Spessore formato mm	Peso teorico unit. Kg	Stato fisico			
			H111	0	H32	H34
EN AW-5083 2	1000x2000	10,80	✓			
EN AW-5083 3	1500x3000	36,40	✓			
EN AW-5083 4	1000x2000	21,60	✓			
EN AW-5083 4	1250x2500	33,70	✓			
EN AW-5083 4	2000x6000	129,60	✓			
EN AW-5083 5	1000x2000	27,00	✓			
EN AW-5083 5	1250x2500	42,30	✓			
EN AW-5083 5	1500x3000	60,70	✓			
EN AW-5083 5	2000x3000	81,00	✓			
EN AW-5083 5	2000x4000	108,00	✓			
EN AW-5083 5	2000x6000	162,00	✓			
EN AW-5083 6	1000x2000	32,40	✓			
EN AW-5083 6	1250x2500	50,60	✓			
EN AW-5083 6	1500x3000	72,90	✓			
EN AW-5083 6	2000x6000	194,40	✓			
EN AW-5083 8	1000x2000	43,20	✓			
EN AW-5083 8	1500x3000	97,20	✓			
EN AW-5083 8	2000x6000	259,20	✓			
EN AW-5083 10	1250x2500	84,30	✓			
EN AW-5083 10	1500x3000	121,50	✓			
EN AW-5083 10	2000x6000	325,20	✓			
EN AW-5083 12	1500x3000	145,80	✓			
EN AW-5083 15	1000x2000	81,60	✓			
EN AW-5083 15	1250x2500	126,50	✓			
EN AW-5083 15	1500x3000	127,50	✓			
EN AW-5083 15	2000x6000	489,60	✓			
EN AW-5083 20	1000x2000	108,80	✓			
EN AW-5083 20	1250x2500	168,70	✓			
EN AW-5083 20	1500x3000	243,00	✓			
EN AW-5083 25	1000x2000	135,00	✓			
EN AW-5083 25	1500x3000	304,00	✓			
EN AW-5083 30	1000x2000	162,60	✓			
EN AW-5083 30	1250x2500	253,00	✓			
EN AW-5083 30	1500x3000	365,85	✓			
EN AW-5083 40	1000x2000	216,00	✓			
EN AW-5083 50	1000x2000	271,00	✓			
EN AW-5083 60	1500x3000	729,00	✓			
EN AW-5083 80	1250x2500	675,00	✓			

AnTicORdAL en AW-6082

Fil ti | i ti di II i i | t III F i F s

LAMieRe dA nASTRO, dA cOSTRUZIOne PIASTRe TeMPeRATE

Spessore mm	Formato mm	Peso teorico unit. Kg	Stato fisico			
			T6	T651		
0,8	1000x2000	2,16	✓			
1	1000x2000	5,40	✓			
1	1500x3000	12,15	✓			
1,5	1000x2000	8,10	✓			
1,5	1250x2500	12,66	✓			
2	1000x2000	10,80	✓			
2	1500x3000	24,30	✓			
2,5	1000x2000	13,50	✓			
3	1000x2000	16,20	✓			
3	1250x2500	25,31	✓			
3	1500x3000	36,45	✓			
4	1000x2000	21,60	✓			
4	1250x2500	33,80	✓			
4	1500x3000	48,60	✓			
5	1000x2000	27,00	✓			
5	1500x3000	60,75	✓			
6	1000x2000	32,40	✓			
6	1250x2500	50,60	✓			
6	1500x3000	72,90	✓			
8	1000x2000	43,00	✓			
8	1500x3000	97,20	✓			
10	1000x2000	54,00	✓			
10	1250x2500	84,30	✓			
10	1500x3000	121,50	✓			
12	1000x2000	64,80	✓			
12	1250x2500	101,00	✓			
12	1500x3000	145,80	✓			
15	1000x2000	81,00	✓			
15	1250x2500	136,50	✓			
15	1500x3000	182,50	✓			
20	1000x2000	108,00	✓			
20	1250x2500	168,70	✓			
20	1500x3000	243,00	✓			
25	1000x2000	135,00	✓			
25	1250x2500	211,00	✓			
25	1500x3000	303,75	✓			
30	1000x2000	162,00	✓			
30	1250x2500	253,00	✓			
30	1500x3000	364,50	✓			
35	1000x2000	189,00	✓			
35	1250x2500	295,31	✓			
35	1500x3000	425,30	✓			

LAMieRe dA nASTRO, dA cOSTRUZIOne PIASTRe TeMPeRATE

Spessore mm	Formato mm	Peso teorico unit. Kg	Stato fisico			
			T6	T651		
40	1000x2000	216,00	✓			
40	1250x2500	337,50	✓			
40	1500x3000	486,00	✓			
45	1500x3000	546,75	✓			
50	1000x2000	270,00	✓			
50	1250x2500	421,80	✓			
50	1500x3000	607,50	✓			
60	1000x2000	324,00	✓			
60	1250x2500	506,00	✓			
60	1500x3000	729,00	✓			
70	1000x2000	378,00	✓			
70	1250x2500	590,60	✓			
70	1500x3000	850,50	✓			
80	1000x2000	432,00	✓			
80	1250x2500	675,00	✓			
80	1500x3000	972,00	✓			
90	1250x2500	759,30	✓			
100	1000x2000	540,00	✓			
100	1250x2500	844,00	✓			
120	1250x2500	1012,00	✓			

MALTERINI A.
METALFERRO

ALLUMiniO - BARRe TOnde

LEGA EN AW-2011 (afilato sino a diam. 65)
LEGA EN AW-2030
LEGA EN AW-6060
LEGA EN AW-6082
LEGA EN AW-2007
LEGA EN AW-6012 (afilato sino a diam. 65)



Ø d mm	Peso teorico Kg/Ml	Lega				
		en AW 2011	en AW 2030	en AW 6060	en AW 6082	en AW 6012
5	0,053	✓				
6	0,076	✓		✓	✓	
7	0,104	✓				
8	0,136	✓		✓		
9	0,172	✓				
10	0,21	✓		✓	✓	
11	0,25	✓				
12	0,30	✓		✓		
13	0,36	✓		✓		
14	0,42	✓		✓	✓	
15	0,48	✓		✓	✓	
16	0,54	✓		✓	✓	✓
17	0,61	✓				
18	0,69	✓		✓	✓	✓
19	0,77	✓				
20	0,84	✓		✓	✓	✓
21	0,97	✓				
22	1,03	✓				
23	1,12	✓			✓	
24	1,22	✓				
25	1,33	✓		✓	✓	✓
26	1,43	✓				
27	1,55	✓				
28	1,66	✓				
30	1,91	✓			✓	✓
32	2,17	✓				✓
34	2,55	✓				
35	2,60	✓			✓	✓
36	2,75	✓				
37	3,010					✓
38	3,06	✓				
40	3,39	✓			✓	✓
42	3,74	✓				✓
44	4,257	✓				✓
45	4,30	✓			✓	✓
46	4,653	✓				
48	4,89	✓				
50	5,30	✓			✓	✓
52	5,80	✓				
55	6,655	✓			✓	✓
55	6,655	✓				
58	7,130	✓			✓	✓
60	7,63	✓				
60	7,63	✓				✓
62	8,46	✓				
65	9,295	✓				✓
65	9,295	✓	✓		✓	✓

Ø d mm	Peso teorico Kg/Ml	Lega				
		en AW 2011	en AW 2030	en AW 2007	en AW 6082	en AW 6012
70	10,39	✓			✓	✓
75	11,93	✓			✓	✓
80	13,58	✓			✓	✓
85	15,32	✓			✓	✓
90	17,18	✓			✓	✓
95	19,14	✓			✓	✓
100	21,21	✓			✓	✓
105	23,38	✓			✓	✓
110	25,66	✓			✓	✓
115	28,05	✓			✓	✓
120	30,54	✓			✓	
125	33,13	✓			✓	✓
130	35,84	✓			✓	
135	36,65					
140	41,54	✓	✓		✓	
145	44,59					
150	47,71	✓			✓	✓
152	49,17					
160	54,29	✓		✓	✓	
170	61,29	✓			✓	✓
180	68,71	✓			✓	
190	78,948	✓				
195	80,64				✓	
200	84,78	✓			✓	
210	93,68	✓	✓		✓	
220	102,64	✓	✓		✓	
230	112,18		✓		✓	
240	122,00	✓				
250	132,47		✓		✓	
260	143,35				✓	
280	166,25	✓	✓	✓		
300	190,85	✓	✓	✓		
320	223,87			✓		
350	260,00			✓		
360	275,00			✓		
400	340,00			✓		
450	430,00			✓		

✓ PRODOTTO ESTRUSO

MALTERINI A. METALFERRO

BARRE ESAGONALI

prodotti e laminati di alluminio | metalli ferrosi e non ferrosi

LEGA EN AW-2011



c m/m	Peso teorico Kg/M	Lega			
		en AW 2011			
7	0,115	✓			
10	0,234	✓			
12	0,35	✓			
13	0,42	✓			
14	0,48	✓			
15	0,55	✓			
17	0,70	✓			
18	0,79	✓			
19	0,88	✓			
20	0,98	✓			
22	1,18	✓			
24	1,50	✓			
25	1,52	✓			
27	1,78	✓			
28	1,92	✓			
30	2,18	✓			
32	2,39	✓			
35	2,98	✓			
36	3,15	✓			
50	6,08	✓			

BARRE QUADRE


LEGA EN AW-2011 (afilato fino al 60)

LEGA EN AW-2030

LEGA EN AW-6060

LEGA EN AW-6082

LEGA EN AW-2011 estruso (da 25 al 130)



L m/m	Peso teorico Kg/M	Lega			
		en AW 2011	en AW 2030	en AW 6060	en AW 6082
7	0,132	✓			
8	0,173			✓	
10	0,27			✓	
12	0,39	✓		✓	
14	0,53			✓	
15	0,61	✓		✓	✓
16	0,69	✓			
18	0,88	✓			
20	1,08	✓		✓	✓
22	1,31	✓			
25	1,69	✓		✓	✓
30	2,43	✓		✓	✓
32	2,76				
35	3,31	✓		✓	✓
40	4,32	✓		✓	✓
45	5,47	✓			✓
50	6,75	✓			✓
55	8,17	✓			✓
60	9,72	✓			✓
65	11,41				✓
70	13,20	✓			✓
80	17,30	✓	✓		✓
85	19,51				
90	21,87	✓	✓		✓
95	24,64				
100	28,00	✓	✓		✓
110	32,67	✓			✓
115	37,03	✓			
120	38,88	✓	✓		✓
125	43,75	✓			
130	47,50	✓			✓
140	52,92				✓
150	60,75		✓		✓
160	69,12				✓
170	78,03				
180	87,48				✓
190	97,47				
200	108,00	✓			

ALLUMiniO - BARRe PiATTe

LEGA EN AW-2011
LEGA EN AW-6060
LEGA EN AW-6082



L m/m		S Peso teorico Kg/M	Lega		
			en AW 2011	en AW 6060	en AW 6082
8	5	0,108		✓	
10	2	0,054		✓	
10	3	0,081		✓	
10	4	0,108		✓	
10	5	0,135		✓	
10	6	0,162		✓	
10	8	0,216		✓	
15	2	0,081		✓	
15	3	0,122		✓	
15	4	0,162		✓	
15	5	0,202		✓	
15	6	0,243		✓	
15	8	0,324		✓	
15	10	0,405		✓	
20	2	0,108		✓	
20	3	0,162		✓	
20	4	0,216		✓	
20	5	0,270		✓	
20	6	0,234		✓	
20	8	0,432		✓	
20	10	0,540		✓	
20	12	0,648		✓	
20	15	0,810	✓	✓	
25	2	0,135		✓	
25	3	0,202		✓	
25	4	0,270		✓	
25	5	0,337		✓	
25	6	0,405		✓	
25	8	0,540		✓	
25	10	0,675		✓	
25	12	0,810			
25	15	1,012		✓	
25	20	1,350	✓	✓	
30	2	0,162		✓	
30	3	0,243		✓	
30	4	0,324		✓	
30	5	0,405		✓	
30	6	0,486		✓	
30	8	0,648		✓	

L m/m		S Peso teorico Kg/M	Lega		
			en AW 2011	en AW 6060	en AW 6082
30	10	0,810		✓	
30	12	0,972		✓	
30	15	1,215		✓	
30	20	1,620		✓	✓
30	25	2,025		✓	✓
35	3	0,283		✓	
35	4	0,378		✓	
35	5	0,472		✓	
35	6	0,567		✓	
35	8	0,756		✓	
35	10	0,945		✓	
35	15	1,417			✓
35	20	1,890		✓	✓
35	25	2,362			✓
40	2	0,216		✓	
40	3	0,324		✓	
40	4	0,432		✓	
40	5	0,540		✓	
40	6	0,648		✓	
40	8	0,864		✓	
40	10	1,080		✓	✓
40	12	1,296		✓	✓
40	15	1,620		✓	✓
40	20	2,160	✓	✓	✓
40	25	2,70	✓	✓	✓
40	30	3,24	✓		✓
45	3	0,364		✓	
45	5	0,607		✓	
45	6	0,729		✓	
45	15	1,823			✓
50	2	0,270		✓	
50	3	0,405		✓	
50	4	0,540		✓	
50	5	0,675		✓	
50	6	0,810		✓	
50	8	1,08		✓	
50	10	1,35		✓	✓
50	12	1,62		✓	✓
50	15	2,025		✓	✓

ALTERINI A.
METALFERRO

LEGA EN AW-2011
LEGA EN AW-6060
LEGA EN AW-6082



L m/m		S Peso teorico Kg/M	Lega		
			en AW 2011	en AW 6060	en AW 6082
50	20	2,70		✓	✓
50	25	3,375	✓	✓	✓
50	30	4,05	✓	✓	✓
50	40	5,4	✓		✓
60	2	0,324		✓	
60	3	0,486		✓	
60	4	0,648		✓	
60	5	0,81		✓	
60	6	0,972		✓	
60	8	1,296		✓	
60	10	1,62		✓	✓
60	12	1,944		✓	
60	15	2,43		✓	✓
60	20	3,24		✓	✓
60	25	4,05		✓	✓
60	30	4,86	✓	✓	✓
60	35	5,67			✓
60	40	6,48	✓	✓	✓
60	50	8,10			✓
65	6	1,053		✓	
70	5	0,945		✓	
70	6	1,134		✓	
70	8	1,512		✓	
70	10	1,89		✓	✓
70	12	1,27		✓	
70	15	2,835		✓	✓
70	20	3,78			✓
70	25	4,724			✓
70	30	5,67			✓
70	40	7,56			✓
70	50	9,45			✓
70	60	11,34			✓
75	32	6,48		✓	
80	3	0,648		✓	
80	4	0,864		✓	
80	5	1,08		✓	
80	6	1,296		✓	
80	8	1,728		✓	
80	10	2,16		✓	✓
80	12	2,592			✓

L m/m		S Peso teorico Kg/M	Lega		
			en AW 2011	en AW 6060	en AW 6082
80	15	3,243		✓	✓
80	20	4,32		✓	✓
80	25	5,40	✓		✓
80	30	6,48	✓		✓
80	40	8,64	✓		✓
80	50	10,80	✓		✓
80	60	12,96	✓		✓
90	10	2,43		✓	✓
90	12	2,916			✓
90	15	3,645			✓
90	20	4,86			✓
90	30	7,29			
90	40	9,72			✓
90	50	12,15	✓		✓
90	60	14,58	✓		
90	70	17,01	✓		
100	3	0,81		✓	
100	5	1,35		✓	
100	6	1,62		✓	
100	8	2,16		✓	
100	10	2,70		✓	✓
100	12	3,24			✓
100	15	4,05		✓	✓
100	20	5,40		✓	✓
100	25	6,75		✓	✓
100	30	8,10	✓	✓	✓
100	40	10,80	✓		✓
100	50	13,50	✓		✓
100	60	16,20			✓
100	80	21,60			✓
120	5	1,62		✓	
120	8	2,59		✓	
120	10	3,24		✓	✓
120	12	3,89		✓	✓
120	15	4,86		✓	✓
120	20	6,48			✓
120	25	8,10			✓
120	30	9,72			✓
120	40	12,96			✓
120	50	16,20			✓

ALLUMiniO - BARRe PiATTe


LEGA EN AW-2011
LEGA EN AW-6060
LEGA EN AW-6082



L m/m		S teorico Kg/M	Lega		
			en AW 2011	en AW 6060	en AW 6082
120	60	19,44			✓
130	30	10,53			✓
130	60	21,06			
150	8	3,24			
150	10	4,05		✓	✓
150	12	4,86			✓
150	15	6,075		✓	✓
150	20	8,10		✓	✓
150	25	10,13			✓
150	30	12,15			✓
150	40	16,20			✓
150	50	20,20			✓
150	60	24,30			✓
150	80	32,40			
150	100	40,50			✓
180	10	4,86			✓
200	10	5,40		✓	✓
200	12	6,48			✓
200	15	8,10		✓	✓
200	20	10,80			✓
200	25	13,50			✓
200	30	16,20	✓		✓
200	40	21,60			✓
200	50	27,00			✓
200	60	32,40			
200	100	54,00			
210	30	17,01		✓	
250	10	6,747			✓
250	12	8,10			✓
250	15	10,125			✓
250	20	13,50			✓
250	25	16,88			✓
250	30	20,25			✓
250	40	27,00			✓
250	60	40,50			
250	100	67,50			
280	30	22,68			✓
300	15	12,15			
300	20	16,20			✓
300	35	28,35			
310	25	20,93			

MALTERINI A.
METALFERRO

ALLUMiniO - TUBi TOnDi



LEGA EN AW-6060

d m/m		Peso teorico Kg/M	Lega	
			en AW 6060	en AW 6063
6	1	0,042	✓	
7	1	0,051		
8	1	0,060	✓	
10	1	0,076	✓	
10	1,5	0,107	✓	
10	2	0,136	✓	
12	1	0,093	✓	
12	1,5	0,133	✓	
12	2	0,170		
14	1	0,110	✓	
14	1,5	0,158	✓	
14	2	0,203	✓	
14	3,5	0,312	✓	
15	1	0,119	✓	
15	1,5	0,172	✓	
15	2	0,221	✓	
16	1	0,127	✓	
16	1,5	0,184	✓	
16	1,8	0,225		
16	2	0,238	✓	
17	1,5	0,196		
18	1	0,144	✓	
18	1,5	0,209	✓	
18	2	0,272	✓	
20	1	0,161	✓	
20	1,5	0,235	✓	
20	2	0,306	✓	
22	1	0,178	✓	
22	1,5	0,260	✓	
22	2	0,339	✓	
24	1,5	0,285	✓	
25	1	0,204	✓	
25	1,2	0,242		
25	1,5	0,298	✓	
25	2	0,390	✓	
25	2,5	0,477	✓	
25	3	0,560	✓	
25	5	0,848	✓	
26	1	0,212	✓	
26	2	0,407	✓	
28	1	0,229		
28	1,5	0,336	✓	
28	2	0,441	✓	
30	1	0,246	✓	
30	1,5	0,362	✓	
30	2	0,475	✓	
30	2,5	0,583	✓	
30	3	0,687	✓	
30	5	1,060	✓	


d m/m		Peso teorico Kg/M	Lega	
			en AW 6060	en AW 6063
30	7,5	1,470	✓	
32	1	0,263	✓	
32	1,5	0,387	✓	
35	1	0,289	✓	
35	1,5	0,427	✓	
35	2	0,560	✓	
35	2,5	0,689	✓	
35	3	0,814	✓	
35	5	1,272	✓	
36	3	0,850		
38	1,5	0,464		
38,6	1,5	0,472	✓	
40	1	0,331		
40	1,5	0,489	✓	
40	2	0,645	✓	
40	2,5	0,795	✓	
40	3	0,942	✓	
40	4	1,221		
40	5	1,485	✓	
40	10	2,545	✓	
41	1,5	0,503		
45	1,5	0,554	✓	
45	2	0,730	✓	
45	2,5	0,901		
45	3	1,069		
45	10	2,969	✓	
48	2	0,780		
48	2,5	0,964		
50	1	0,416		
50	1,5	0,617	✓	
50	2	0,814	✓	
50	3	1,196	✓	
50	5	1,909	✓	
50	10	3,393	✓	
50	15	4,451	✓	✓
55	1,5	0,681	✓	
55	2	0,899	✓	
55	5	2,127	✓	
55	7,5	3,02	✓	
58	10	4,08	✓	
60	1	0,500	✓	
60	1,5	0,744	✓	
60	2	0,984	✓	
60	3	1,450	✓	
60	4	1,900		
60	5	2,333	✓	
60	7	3,147		
60	8	3,527		
60	10	4,239	✓	
65	1,5	0,808		
65	2	1,030	✓	
65	7,5	3,656	✓	
65	10	4,663	✓	✓
65	12,5	5,564		

d m/m		Peso teorico Kg/M	Lega	
			en AW 6060	en AW 6063
70	1,5	0,871	✓	
70	2	1,154	✓	
70	3	1,705		
70	5	2,758	✓	
70	10	5,3	✓	
75	2	1,238	✓	
75	2,5	1,516	✓	
75	12,5	6,623	✓	
80	1	0,670	✓	
80	1,2	0,803	✓	
80	1,5	0,999		
80	2	1,323	✓	
80	3	1,960	✓	
80	5	3,181	✓	
80	10	5,938	✓	
80	15	8,3	✓	✓
80	20	10,174	✓	
85	2	1,407	✓	
85	2,5	1,750	✓	
85	5	3,391	✓	
90	2	1,493	✓	
90	2,5	1,856	✓	
90	5	3,605	✓	
90	10	6,786	✓	
90	20	11,869	✓	
90	22,5	12,587	✓	✓
95	2,5	1,962	✓	
100	1,2	1,005		
100	2	1,663	✓	
100	2,5	2,068	✓	
100	3	2,469	✓	
100	5	4,029	✓	
100	10	7,634	✓	
100	15	10,80	✓	
101	18,5	12,00	✓	
105	2,5	2,174	✓	
106	3	2,620	✓	
110	2	1,831	✓	
110	2,5	2,30	✓	
110	5	4,451	✓	
110	30	21,319	✓	✓
115	2,5	2,393	✓	
115	10	5,070		
120	2	2,001	✓	
120	3	2,976	✓	
120	5	4,877	✓	
120	35	26,379	✓	✓
130	2,5	2,702	✓	
130	25	22,255	✓	✓
140	4	4,613	✓	
140	5	5,724	✓	
150	3	3,747	✓	
150	5	6,148	✓	
150	10	11,875	✓	
160	10	12,724	✓	

ALLUMiniO - TUBi QUAdRi

ALLUMiniO - TUBi RETT.

ALLUMiniO - PROFiLi eSTRUSi




LEGA EN AW-6060






LEGA EN AW-6060

L m/m	S	Peso teorico Kg/M	Lega en AW 6060
12	1	0,120	✓
15	1,5	0,220	✓
20	1,5	0,299	✓
20	2	0,389	✓
25	2	0,496	✓
30	2	0,604	✓
30	3	0,875	✓
35	1,5	0,542	✓
35	2	0,712	✓
40	1,5	0,580	✓
40	2	0,820	✓
40	3	1,199	✓
40	4	1,555	✓
45	2	0,929	✓
50	2	1,086	✓
50	3	1,523	✓
50	4	1,987	✓
50	5	2,430	✓
60	2	1,252	✓
60	3	1,846	✓
60	4	2,419	✓
70	2	1,469	✓
80	2	1,684	✓
80	4	3,283	✓
90	2,5	2,362	✓
100	2	2,700	✓
100	4	4,147	✓
150	2,5	3,980	✓

L m/m	H m/m	S	Peso teorico Kg/M	Lega en AW 6060
20	10	1,5	0,231	✓
20	15	2	0,335	✓
25	15	1,5	0,299	✓
25	20	2	0,443	✓
30	10	1,5	0,299	✓
30	10	2	0,389	✓
30	15	1,5	0,340	✓
30	15	2	0,442	✓
30	20	1,5	0,380	✓
30	20	2	0,496	✓
35	20	2	0,551	✓
40	15	1,5	0,421	✓
40	15	2	0,551	✓
40	20	1,5	0,461	✓
40	20	2	0,604	✓
40	20	4	1,123	✓
40	25	2	0,659	✓
40	30	2	0,713	✓
50	15	2	0,659	✓
50	20	2	0,715	✓
50	25	2	0,766	✓
50	30	2	0,821	✓
50	30	3	1,199	✓
50	40	2	0,928	✓
60	20	2	0,820	✓
60	30	2	0,938	✓
60	30	3	1,361	✓
60	40	2	1,037	✓
60	40	3	1,523	✓
60	40	4	1,987	✓
80	15	1,5	0,745	✓
80	20	2	1,037	✓
80	30	2	1,144	✓
80	40	2	1,250	✓
80	40	3	1,847	✓
80	40	4	2,422	✓
80	50	2	1,360	✓
80	50	4	2,635	✓
80	60	4	2,851	✓
100	20	2	1,253	✓
100	30	2	1,360	✓
100	30	3	2,009	✓
100	40	2	1,474	✓
100	50	2	1,576	✓
100	50	3	2,333	✓
100	50	4	3,067	✓
120	20	2	1,468	✓
120	40	2	1,684	✓
150	50	3	3,142	✓



profilati e laminati di alluminio | metalli ferrosi e non ferrosi



B m/m	H m/m	S	Peso teorico Kg/M
20	20	2	0,205
25	25	2	0,260
30	30	2	0,314
40	40	2	0,421
40	20	2	0,313
40	40	4	0,842
50	50	2	0,529
50	50	5	1,282

B m/m	H m/m	S	Peso teorico Kg/M
15	15	1,5	0,170
20	15	2	0,248
20	20	2	0,302
25	25	2	0,385
30	20	2	0,357
30	30	2	0,465
35	35	2	0,545
40	20	2	0,410
40	40	2	0,626
40	40	4	1,209
45	20	2	0,427
45	30	2	0,545
50	20	2	0,460
50	20	2	0,470
50	50	2	0,788
50	50	5	1,890
100	50	5	2,565
120	60	9	5,400

B m/m	H m/m	S	Peso teorico Kg/M
20	10	2	0,154
20	15	2	0,181
25	15	2	0,206
25	20	2	0,236
30	15	2	0,233
30	20	2	0,259
30	20	3	0,380
35	15	2	0,259
40	20	2	0,313
40	20	3	0,462
40	20	4	0,605
40	30	2	0,367
40	30	3	0,542
50	20	2	0,368
50	25	2	0,395
50	30	5	1,014
60	20	2	0,422
60	30	2	0,475
60	30	3	0,705
60	30	4	0,928
60	40	3	0,785
60	40	4	1,036
60	40	5	1,282
80	20	2	0,530
80	40	2	0,637
80	40	4	1,253
80	40	6	1,847
100	20	2	0,640
100	50	2	0,800
100	50	5	1,957

B m/m	H m/m	S	Peso teorico Kg/M
15	15	1,5	0,115
15	15	2	0,151
15	15	3	0,219
20	20	1,5	0,156
20	20	2	0,205
20	20	3	0,300
25	25	2	0,260
25	25	3	0,380
30	30	2	0,313
30	30	3	0,462
30	30	4	0,605
35	35	2	0,367
35	35	5	0,877
40	40	2	0,421
40	40	3	0,624
40	40	4	0,821
40	40	5	1,012
50	50	2	0,530
50	50	3	0,786
50	50	4	1,037
50	50	5	1,282
50	50	6	1,583
50	50	10	2,43
60	60	2	0,637
60	60	3	0,948
60	60	4	1,253
60	60	5	1,553
60	60	6	1,847
80	80	4	1,685
80	80	6	2,495
80	80	8	3,284
100	100	10	5,130

ALTERINI A.
ETALFERRO
INOX SAN ZENO - AREZZO